

Date: 20/04/2022

TIMCO SDS Ref No. SDS-04-PUF-05 / v1

Fill & Fix PU Foam Cleaner - Safety Data Sheet

According to 1907/2006/EC, Article 31

SECTION 1: Identifica tion of the substance/mixture and of the company/undertaking

· 1.1 Product identifier

Product Name: Fill & Fix PU Foam Cleaner

Product Code: 247893

UFI: 1QH4-HQMA-4006-QE6K

Trade name: Cleaner

· 1.2 Relevant identified uses of the substance or mixture and

Construction chemicals

· Application of the substance / the mixture Remover

Supplier: T.I Midwood & Co. Ltd

TIMCO House Green Lane Wardle Nantwich CW5 6BJ ises advised against

T.I Midwood & Co. Ltd Aviemore House

Hill Street Monahan Ireland

Emergency Help Line: 01865 407333 (24 hour service)

SECTION 2: Hazards identification

- · 2.1 Classification of the substance or mixture
- · Classification according to Regulation (EC) No 1272/2008



GHS02 flame

Aerosol 1 H222-H229 Extremely flammable aerosol. Pressurised container: May burst if heated.



GHS07

Eye Irrit. 2 H319 Causes serious eye irritation.

STOT SE 3 H336 May cause drowsiness or dizziness.

- · 2.2 Label elements
- · Labelling according to Regulation (EC) No 1272/2008

The product is classified and labelled according to the CLP regulation.

· Hazard pictograms





GHS02 GHS07

- · Signal word Danger
- · Hazard-determining components of labelling: ethyl acetate

According to 1907/2006/EC, Article 31

· Hazard statements

H222 Extremely flammable aerosol.

H229 Pressurised container: May burst if heated.

H319 Causes serious eye irritation.

H336 May cause drowsiness or dizziness.

· Precautionary statements

P102 Keep out of reach of children. P261

Avoid breathing spray.

P271 Use only outdoors or in a well-ventilated area.

P280 Wear protective gloves/protective clothing/eye protection/face protection.

P305+P351+P338 IF IN EYES: Rinse cautiously with water for several minutes. Remove contact lenses, if

present and easy to do. Continue rinsing.

P337+P313 If eye irritation persists: Get medical advice/attention.

P403+P233 Store in a well-ventilated place. Keep container tightly closed.

P501 Dispose of contents/container in accordance with local/regional/national/international

regulations.

· Additional information:

Do not pierce or burn, even after use.

Protect from sunlight. Do not expose to temperatures exceeding 50 °C/122 °F.

Do not spray on an open flame or other ignition source.

Keep away from heat, hot surfaces, sparks, open flames and other ignition sources. No smoking.

EUH066 Repeated exposure may cause skin dryness or cracking. • 2.3 Other hazards

Results of PBT and vPvB assessment

· PBT: Not applicable.

· vPvB: Not applicable.

SECTION 3: Composition/information on ingredients

- 3.2 Chemical characterisation: Mixtures
- · Description: Mixture of substances listed below with nonhazardous additions.

Dangerous components:		
CAS: 67-64-1 EINECS: 200-662-2 Reg.nr.: 01-2119471330-49-xxxx	acetone Flam. Liq. 2, H225; Eye Irrit. 2, H319; STOT SE 3, H336	19.0 - 34.0%
CAS: 141-78-6 EINECS: 205-500-4 Reg.nr.: 01-2119475103-46-xxxx	ethyl acetate Flam. Liq. 2, H225; Eye Irrit. 2, H319; STOT SE 3, H336	19.0 - 34.0%
CAS: 67-63-0 EINECS: 200-661-7 Reg.nr.: 01-2119457558-25-XXXX	propan-2-ol Flam. Liq. 2, H225; Eye Irrit. 2, H319; STOT SE 3, H336	9.0 - 19.0%
CAS: 74-98-6 EINECS: 200-827-9 Reg.nr.: 01-21194869440-21-xxxx	propane Flam. Gas 1, H220; Press. Gas (Comp.), H280	< 10.0%
CAS: 106-97-8 EINECS: 203-448-7 Reg.nr.: 01-2119474691-31-xxxx	butane Flam. Gas 1, H220; Press. Gas (Comp.), H280	< 10.0%

According to 1907/2006/EC, Article 31

CAS: 75-28-5 isobutane < 10.0% EINECS: 200-857-2 Flam. Gas 1, H220; Press. Gas (Comp.), H280 < 10.0%

· Additional information: For the wording of the listed hazard phrases refer to section 16.

SECTION 4: First aid measures

- · 4.1 Description of first aid measures
- General information: Immediately remove any clothing soiled by the product.
- · After inhalation:

Supply fresh air and to be sure call for a doctor.

Use a respiratory bag or breathing device.

In case of unconsciousness place patient stably in side position for transportation.

- · After skin contact: Immediately wash with water and soap and rinse thoroughly.
- After eye contact:

Rinse opened eye for several minutes under running water. If symptoms persist, consult a doctor.

· After swallowing:

Rinse out mouth and then drink plenty of water.

Do not induce vomiting; call for medical help immediately.

· 4.2 Most important symptoms and effects, both acute and delayed

Stupor.

Headache.

Unconsciousness.

Coughing.

Nausea.

Dizziness.

· 4.3 Indication of any immediate medical attention and special treatment needed

No further relevant information available.

SECTION 5: Firefighting measures

- · 5.1 Extinguishing media
- · Suitable extinguishing agents:

Carbon dioxide.

Water spray.

Fire-extinguishing powder.

Alcohol resistant foam.

- · For safety reasons unsuitable extinguishing agents: Water with full jet.
- · 5.2 Special hazards arising from the substance or mixture

Can form explosive gas-air mixtures.

Formation of toxic gases is possible during heating or in case of fire.

- 5.3 Advice for firefighters
- · Protective equipment:

Do not inhale explosion gases or combustion gases. Wear self-contained respiratory protective device.

Additional information Cool endangered receptacles with water spray.

SECTION 6: Accidental release measures

• 6.1 Personal precautions, protective equipment and emergency procedures Keep away from ignition sources.

According to 1907/2006/EC, Article 31

Do not breathe gas / fumes / vapour / spray.

Use respiratory protective device against the effects of fumes / dust / aerosol. Wear protective equipment. Keep unprotected persons away.

- · 6.2 Environmental precautions: Do not allow to enter sewers / surface or ground water.
- · 6.3 Methods and material for containment and cleaning up:

Allow to evaporate.

Ensure adequate ventilation.

• **6.4 Reference to other sections** See Section 13 for disposal information.

SECTION 7: Handling and storage

· 7.1 Precautions for safe handling

Ensure good interior ventilation, especially at floor level. (Fumes are heavier than air).

Ensure good ventilation / exhaustion at the workplace. Open and handle receptacle with care.

· Information about fire - and explosion protection:

Keep ignition sources away - Do not smoke.

Protect against electrostatic charges.

Pressurised container: protect from sunlight and do not expose to temperatures exceeding 50°C, i.e. electric lights. Do not pierce or burn, even after use.

Do not spray onto a naked flame or any incandescent material.

- · 7.2 Conditions for safe storage, including any incompatibilities
- · Storage:
- · Requirements to be met by storerooms and receptacles:

Store in a cool location.

Observe official regulations on storing packagings with pressurised containers.

· Information about storage in one common storage facility:

Store away from oxidising agents.

Do not store together with reducing agents, heavy-metal compounds, acids and alkalis.

Further information about storage conditions:

Store in vertical position in closed original containers.

Store at temperature from +5°C to +30°C.

Protect from heat and direct sunlight.

Store under lock and key and out of the reach of children.

· 7.3 Specific end use(s) No further relevant information available.

SECTION 8: Exposure controls/personal protection

- · Additional information about design of technical facilities: No further data; see item 7.
- · 8.1 Control parameters

· Ingre	Ingredients with limit values that require monitoring at the workplace:			
CAS:	67-64-1 acetone			
WEL	Short-term value: 3620 mg/m³, 1500 ppm Long-term value: 1210 mg/m³, 500 ppm			
CAS:	141-78-6 ethyl acetate			
WEL	Short-term value: 400 ppm Long-term value: 200 ppm			
CAS:	67-63-0 propan-2-ol			
WEL	Short-term value: 1250 mg/m³, 500 ppm Long-term value: 999 mg/m³, 400 ppm			

According to 1907/2006/EC, Article 31

	/				
CAS: 106-	-97-8 b	utane			
WEL Sho	rt-term	value: 1810 mg/m³, 750 ppm			
	Long-term value: 1450 mg/m³, 600 ppm				
	c (if mo	re than 0.1% of buta-1.3-diene)			
· DNELs					
CAS: 67-6	34-1 ac	etone			
Dermal	DNEL	62 mg/kg/day (General population, consumers)			
		186 mg/kg/day (Workers)			
Inhalative	DNEL	200 mg/m3 (General population, consumers)			
		2420 mg/m3 (Workers)			
CAS: 141-	-78-6 et	thyl acetate			
Oral	DNEL	4.5 mg/kg/day (General population, consumers)			
Dermal	DNEL	37 mg/kg/day (General population, consumers)			
		63 mg/kg/day (Workers)			
Inhalative	DNEL	734 mg/m3 (General population, consumers)			
		1468 mg/m3 (Workers)			
CAS: 67-6	3-0 pro	opan-2-ol			
Oral	DNEL	26 mg/kg/day (General population, consumers)			
Dermal	DNEL	319 mg/kg/day (General population, consumers)			
		888 mg/kg/day (Workers)			
Inhalative	DNEL	89 mg/m3 (General population, consumers)			
500 mg/m3 (Workers)					
· PNECs					
CAS: 67-6	64-1 ac	etone			
(freshwate	er)	10.6 mg/l			
(sea water	r)	1.06 mg/l			
(freshwate	r sedin	30.4 mg/kg			
(sea water	r sedim	30.4 mg/kg			
(soil)		29.5 mg/kg			
CAS: 141	-78-6 e	thyl acetate			
(freshwate		0.26 mg/l			
(sea water	•	0.026 mg/l			
,					
`		0.034 mg/kg			
·		0.22 mg/kg			
CAS: 67-6	3-0 pr				
(freshwate		140.9 mg/l			
(sea water	,	140.9 mg/l			
(freshwater sediments)					
(sea water sediments)		, , , , , , , , , , , , , , , , , , , ,			
(soil)		552 mg/kg			
9.2 Evno					

- · 8.2 Exposure controls
- · Personal protective equipment:
- · General protective and hygienic measures:

Keep away from foodstuffs, beverages and feed.

Immediately remove all soiled and contaminated clothing.

According to 1907/2006/EC, Article 31

Do not eat, drink, smoke or sniff while working.

Avoid contact with the eyes and skin.

· Protection of hands:



Protective gloves

EN 374

The glove material has to be impermeable and resistant to the product / the substance / the preparation. Selection of the glove material on consideration of the penetration times, rates of diffusion and the degradation.

· Material of gloves

Polyethylene gloves.

Recommended thickness of the material: \geq 0.02 mm.

The selection of the suitable gloves does not only depend on the material, but also on further marks of quality and varies from manufacturer to manufacturer. As the product is a preparation of several substances, the resistance of the glove material can not be calculated in advance and has therefore to be checked prior to the application.

Penetration time of glove material

> 10 mir

The exact break trough time has to be found out by the manufacturer of the protective gloves and has to be observed.

· Eye protection:



Tightly sealed goggles

EN 166

- Body protection: Protective work clothing.

SECTION 9: Physical and chemical properties

· 9.1 Information on basic physical and chemical properties

· General Information · Appearance:

Form: Aerosol
Colour: Colorless

Odour: Characteristic

Change in condition

Melting point/freezing point: -160 °C Initial boiling point and boiling range: -12 °C

· Flash point: -10 °C

• Auto-ignition temperature: > +365 °C (butane)

• **Explosive properties:** Heating may cause an explosion.

· Explosion limits:

Oxidising properties Extremely flammable.

· Vapour pressure at 20 °C: > 500 kPa

According to 1907/2006/EC, Article 31

· Density:	Not determined
· Solubility in / Miscibility with	
water:	Soluble
· 9.2 Other information	No further relevant information available

SECTION 10: Stability and reactivity

- 10.1 Reactivity No further relevant information available.
- 10.2 Chemical stability
- · Thermal decomposition / conditions to be avoided:

To avoid thermal decomposition do not overheat.

No decomposition if used according to specifications.

- 10.3 Possibility of hazardous reactions Reacts with oxidising agents.
- 10.4 Conditions to avoid No further relevant information available.
- 10.5 Incompatible materials: No further relevant information available.
- 10.6 Hazardous decomposition products: No dangerous decomposition products known.

SECTION 11: Toxicological information

- · 11.1 Information on toxicological effects
- · Acute toxicity Based on available data, the classification criteria are not met.

· LD/LC50	· LD/LC50 values relevant for classification:			
CAS: 141-	-78-6 ethy	/I acetate		
Oral	LD50	>200 mg/kg (fish)		
		5620 mg/kg (rabbit)		
Inhalative	LC50/4h	1600 mg/l (rat)		
CAS: 67-6	4-1 aceto	one		
Oral	LD50	5800 mg/kg (rat)		
Dermal	LD50	20000 mg/kg (rabbit)		
Inhalative	LC50/4h	7.5 mg/l (fish)		
CAS: 67-6	3-0 propa	an-2-ol		
Oral	LD50	>100 mg/kg (fish)		
		5045 mg/kg (rat)		
Dermal	LD50	12800 mg/kg (rabbit)		
Inhalative	LC50/4h	30 mg/l (rat)		

- · Primary irritant effect:
- · Skin corrosion/irritation Based on available data, the classification criteria are not met.
- · Serious eye damage/irritation Causes serious eye irritation.
- · Respiratory or skin sensitisation Based on available data, the classification criteria are not met.
- · Germ cell mutagenicity Based on available data, the classification criteria are not met.
- Carcinogenicity Based on available data, the classification criteria are not met. Reproductive toxicity Based on available data, the classification criteria are not met.
- STOT-single exposure

May cause drowsiness or dizziness.

- · STOT-repeated exposure Based on available data, the classification criteria are not met.
- · Aspiration hazard Based on available data, the classification criteria are not met.

According to 1907/2006/EC, Article 31

SECTION 12: Ecological information

· 12.1 Toxicity

· Aqua	tic toxicity:
CAS:	67-63-0 propan-2-ol
EC50	>100 mg/kg (daphnia)
CAS:	141-78-6 ethyl acetate
EC50	>700 mg/kg (daphnia)
CAS:	67-64-1 acetone
EC50	10 mg/kg (daphnia)

- 12.2 Persistence and degradability Easily biodegradable
- · 12.3 Bioaccumulative potential Non significant accumulation in organisms
- 12.4 Mobility in soil No further relevant information available.
- · Additional ecological information:
- General notes:

Due to available data on eliminability/decomposition and bioaccumulation potential a prolonged damage of the environment is unlikely.

Water hazard class 1 (German Regulation) (Self-assessment): slightly hazardous for water.

Do not allow undiluted product or large quantities of it to reach ground water, water course or sewage system.

- · 12.5 Results of PBT and vPvB assessment
- · PBT: Not applicable.
- · vPvB: Not applicable.
- 12.6 Other adverse effects No further relevant information available.

SECTION 13: Disposal considerations

- · 13.1 Waste treatment methods
- Recommendation

Do not allow to enter surface or ground water.

Dispose of in a safe manner in accordance with local / national regulations.

Assigning a code from the waste catalogue depends on the sector, in which the user operates, as well as on arrangements made between the waste generator and a competent environment protection department.


Substance/mixture as a waste compound brings hazardous properties HP: 3, 4, 5


Must not be disposed together with household garbage. Do not allow product to reach sewage system.

- · European waste catalogue
 - 15 01 11* metallic packaging containing a hazardous solid porous matrix (for example asbestos), including empty pressure containers
 - · Uncleaned packaging:
 - · Recommendation: Disposal must be made according to official regulations.

SECTION 14: Transport information

- · 14.1 UN-Number
- · ADR, IMDG, IATA UN1950
- · 14.2 UN proper shipping name
- · ADR, IMDG, IATA AEROSOLS





 -	
	
 -	
	
	
	
	
_	
_	
_	
_	
_	
_	
_	
-	
-	
-	
· Class	2 5F Gases.
· Label	2.1
	2.1
14.5 Environmental hazards:	
· Marine pollutant:	No.
· 14.6 Special precautions for user	Warning: Gases.
Danger code (Kemler):	-
· EMS Number:	F-D,S-U
· 14.7 Transport in bulk according to Anne	x II of Marpol
and the IBC Code Not applicable.	
Transport/Additional information:	
· Transport/Additional information:	

According to 1907/2006/EC, Article 31

· ADR	
· Limited quantities (LQ)	1L
· Transport category	2
· Tunnel restriction code	D
· UN "Model Regulation":	UN1950 AEROSOLS, 2.1

SECTION 15: Regulatory information

- · 15.1 Safety, health and environmental regulations/legislation specific for the substance or mixture
- · Directive 2012/18/EU
- · Qualifying quantity (tonnes) for the application of lower-tier requirements 150 t
- · Qualifying quantity (tonnes) for the application of upper-tier requirements 500 t
- · REGULATION (EC) No 1907/2006 ANNEX XVII Conditions of restriction: 3
- · Other regulations, limitations and prohibitive regulations
- Substances of very high concern (SVHC) according to REACH, Article 57 None of the ingredients is listed.
- · 15.2 Chemical safety assessment: A Chemical Safety Assessment has not been carried out.

SECTION 16: Other information

This information is based on our present knowledge. However, this shall not constitute a guarantee for any specific product features and shall not establish a legally valid contractual relationship.

Relevant phrases

H220 Extremely flammable gas.

H225 Highly flammable liquid and vapour.

H280 Contains gas under pressure; may explode if heated.

H319 Causes serious eye irritation.

H336 May cause drowsiness or dizziness.

· Department issuing SDS: Product safety department.

· IMDG, IATA			
4			
-			
_			
-			
-			
-			
=			
_			
_			

·		

		
<u></u>		

ding to 1907/2006,			
			
			
			
<u></u>			
			
 ,_			
			
<u> </u>			
 			
			
			
<u></u>			
 -			
			
			
			
			
			
			
			
			
			
			
			
			
			
			
			

_		
_		
_		
-		
_		
_		
_		
_		

According to 1907/2006/EC, Article 31

Class	2 5F Gases.	
Label	2.1	
14.5 Environmental hazards:		
Marine pollutant:	No.	
14.6 Special precautions for user	Warning: Gases.	
Danger code (Kemler):	-	
EMS Number:	F-D,S-U	
14.7 Transport in bulk according to An	nex II of Marpol	
14.7 Transport in bulk according to An and the IBC Code Not applicable.	nex II of Marpol	
14.7 Transport in bulk according to An and the IBC Code Not applicable. Transport/Additional information:	nex II of Marpol	
14.7 Transport in bulk according to An and the IBC Code Not applicable. Transport/Additional information: ADR	nex II of Marpol	
14.7 Transport in bulk according to An and the IBC Code Not applicable. Transport/Additional information: ADR Limited quantities (LQ)	•	
14.7 Transport in bulk according to An and the IBC Code Not applicable. Transport/Additional information: ADR Limited quantities (LQ) Transport category Tunnel restriction code	1L	

SECTION 15: Regulatory information

- \cdot 15.1 Safety, health and environmental regulations/legislation specific for the substance or mixture
- · Directive 2012/18/EU
- · Qualifying quantity (tonnes) for the application of lower-tier requirements 150 t
- · Qualifying quantity (tonnes) for the application of upper-tier requirements 500 t
- · REGULATION (EC) No 1907/2006 ANNEX XVII Conditions of restriction: 3
- · Other regulations, limitations and prohibitive regulations
- Substances of very high concern (SVHC) according to REACH, Article 57 None of the ingredients is listed.
- 15.2 Chemical safety assessment: A Chemical Safety Assessment has not been carried out.

SECTION 16: Other information

This information is based on our present knowledge. However, this shall not constitute a guarantee for any specific product features and shall not establish a legally valid contractual relationship.

Relevant phrases

H220 Extremely flammable gas.

H225 Highly flammable liquid and vapour.

H280 Contains gas under pressure; may explode if heated.

H319 Causes serious eve irritation.

H336 May cause drowsiness or dizziness.

Department issuing SDS: Product safety department.

According to 1907/2006/EC, Article 31

Abbreviations and acronyms:

ADR: Accord européen sur le transport des marchandises dangereuses par Route (European Agreement concerning the International Carriage of Dangerous Goods by Road)

IMDG: International Maritime Code for Dangerous Goods

IATA: International Air Transport Association

GHS: Globally Harmonised System of Classification and Labelling of Chemicals EINECS: European Inventory of Existing Commercial Chemical Substances ELINCS: European List of Notified Chemical Substances

CAS: Chemical Abstracts Service (division of the American Chemical Society)

DNEL: Derived No-Effect Level (REACH)

PNEC: Predicted No-Effect Concentration (REACH)

LC50: Lethal concentration, 50 percent

LD50: Lethal dose, 50 percent

PBT: Persistent, Bioaccumulative and Toxic SVHC: Substances of Very High Concern vPvB: very Persistent and very Bioaccumulative Flam. Gas 1: Flammable gases - Category 1

Aerosol 1: Aerosols - Category 1

Press. Gas (Comp.): Gases under pressure - Compressed gas

Flam. Liq. 2: Flammable liquids – Category 2

Eye Irrit. 2: Serious eye damage/eye irritation - Category 2

STOT SE 3: Specific target organ toxicity (single exposure) - Category 3

According to 1907/2006/EC, Article 31

11/11

Head Office: TIMCO House, Green Lane, Wardle, Nantwich, CW5 6BJ | Tel: +44 (0)1829 261111 | Fax: +44 (0)1829 261102 | Web: timco.co.uk