

BRIWAX ORIGINAL WAX POLISH

Page: 1 Compilation date: 18/03/2017 Revision date: 22/10/2020

Section 1: Identification of the substance/mixture and of the company/undertaking

1.1. Product identifier

Product name: BRIWAX ORIGINAL WAX POLISH

1.2. Relevant identified uses of the substance or mixture and uses advised against

1.3. Details of the supplier of the safety data sheet

| Company name: | Rustins Ltd |
|---------------|-----------------------|
| | Waterloo Road |
| | Cricklewood |
| | London |
| | NW2 7TX |
| | United Kingdom |
| Tel: | +44 (0)208 450 4666 |
| Fax: | +44 (0)208 452 2008 |
| Email: | rustins@rustins.co.uk |

1.4. Emergency telephone number

| Emergency tel: | +44 (0)208 450 4666 OFFICE HOURS ONLY |
|----------------|---------------------------------------|
| Manufacturer: | Rustins Ltd. |
| | Waterloo Road |
| | Cricklewood |
| | London |
| | NW2 7TX |
| | United Kingdom |
| Tel: | +44 (0)208 450 4666 |
| Fax: | +44 (0)208 452 2008 |
| Email: | rustins@rustins.co.uk |

Section 2: Hazards identification

| 2.1. Classification of the substance or mixture | | |
|---|--|--|
| Classification under CLP: | Skin Irrit. 2: H315; Repr. 2: H361d; STOT RE 2: H373; STOT SE 3: H336; Flam. Liq. 1: | |
| | H224 | |
| Most important adverse effects: | ts: Extremely flammable liquid and vapour. Causes skin irritation. May cause drowsiness or | |
| | dizziness. Suspected of damaging the unborn child. May cause damage to organs | |
| | through prolonged or repeated exposure. | |

BRIWAX ORIGINAL WAX POLISH

Page: 2

| 2.2. Label elements | |
|---------------------------|---|
| Label elements: | |
| UFI: | EYM3-X0YR-2006-WH1C |
| Hazard statements: | H224: Extremely flammable liquid and vapour. |
| | H315: Causes skin irritation. |
| | H336: May cause drowsiness or dizziness. |
| | H361d: Suspected of damaging the unborn child. |
| | H373: May cause damage to organs through prolonged or repeated exposure. |
| Hazard pictograms: | GHS07: Exclamation mark |
| | GHS08: Health hazard |
| | GHS02: Flame |
| | |
| Signal words: | Warning |
| Precautionary statements: | P260: Do not breathe fume. |
| | P280: Wear protective gloves. |
| | P303+P361+P353: IF ON SKIN (or hair): Take off immediately all contaminated clothing. |
| | Rinse skin with water . |
| | P304+P340: IF INHALED: Remove person to fresh air and keep comfortable for |
| | breathing. |
| | P308+P313: IF exposed or concerned: Get medical advice. |
| | P314: Get medical advice/attention if you feel unwell. |
| 2.3. Other hazards | |

Other hazards: In use, may form flammable / explosive vapour-air mixture.

PBT: This product is not identified as a PBT/vPvB substance.

Section 3: Composition/information on ingredients

3.2. Mixtures

Hazardous ingredients:

TOLUENE

| EINECS | CAS | PBT / WEL | CLP Classification | Percent |
|-----------|----------|-----------|--|---------|
| 203-625-9 | 108-88-3 | - | Flam. Liq. 2: H225; Repr. 2: H361d; Asp. Tox. 1: H304; STOT RE 2: H373; Skin Irrit. 2: H315: STOT SE 3: H336 | 70-90% |

Section 4: First aid measures

BRIWAX ORIGINAL WAX POLISH

| | - |
|----------------------------------|--|
| 4.1. Description of first aid me | easures |
| Skin contact: | Remove all contaminated clothes and footwear immediately unless stuck to skin. Wash |
| | immediately with plenty of soap and water. |
| Eye contact: | Bathe the eye with running water for 15 minutes. Consult a doctor. |
| Ingestion: | Wash out mouth with water. Consult a doctor. |
| Inhalation: | Remove casualty from exposure ensuring one's own safety whilst doing so. Consult a |
| | doctor. |
| 4.2. Most important symptoms | s and effects, both acute and delayed |
| Skin contact: | There may be irritation and redness at the site of contact. |
| | There may be irritation and redness. The eyes may water profusely. |
| | There may be soreness and redness of the mouth and throat. |
| | There may be irritation of the throat with a feeling of tightness in the chest. Exposure may |
| | cause coughing or wheezing. |
| Delayed / immediate effects: | Immediate effects can be expected after short-term exposure. |
| 4.3. Indication of any immedia | te medical attention and special treatment needed |
| Immediate / special treatment: | Eye bathing equipment should be available on the premises. |
| Section 5: Fire-fighting measu | |
| | |
| 5.1. Extinguishing media | |
| Extinguishing media: | Suitable extinguishing media for the surrounding fire should be used. |
| 5.2. Special hazards arising fr | om the substance or mixture |
| Exposure hazards: | In combustion emits toxic fumes. |
| 5.3. Advice for fire-fighters | |
| | |
| Advice for fire-fighters: | Wear self-contained breathing apparatus. Wear protective clothing to prevent contact |
| | with skin and eyes. |
| Section 6: Accidental release | measures |
| 6.1. Personal precautions, pro | equipment and emergency procedures |
| Personal precautions: | Refer to section 8 of SDS for personal protection details. If outside do not approach from |
| | downwind. If outside keep bystanders upwind and away from danger point. Mark out the |
| | contaminated area with signs and prevent access to unauthorised personnel. Do not |
| | create dust. |
| | |
| 6.2. Environmental precaution | |
| | |

BRIWAX ORIGINAL WAX POLISH

6.3. Methods and material for containment and cleaning up

Clean-up procedures: Transfer to a closable, labelled salvage container for disposal by an appropriate

method.

6.4. Reference to other sections

Reference to other sections: Refer to section 8 of SDS.

Section 7: Handling and storage

7.1. Precautions for safe handling

Handling requirements: Avoid direct contact with the substance. Ensure there is sufficient ventilation of the area.

Do not handle in a confined space. Avoid the formation or spread of dust in the air.

7.2. Conditions for safe storage, including any incompatibilities

Storage conditions: Store in a cool, well ventilated area. Keep container tightly closed.

Suitable packaging: Must only be kept in original packaging.

7.3. Specific end use(s)

Specific end use(s): No data available.

Section 8: Exposure controls/personal protection

8.1. Control parameters

Hazardous ingredients:

TOLUENE

Workplace exposure limits:

Respirable dust:

| State | 8 hour TWA | 15 min. STEL | 8 hour TWA | 15 min. STEL |
|-------|------------|--------------|------------|--------------|
| UK | 191 mg/m3 | 384 mg/m3 | - | - |

DNEL/PNEC Values

DNEL / PNEC No data available.

8.2. Exposure controls

| Engineering measures: | Ensure there is sufficient ventilation of the area. |
|-------------------------|--|
| Respiratory protection: | Self-contained breathing apparatus must be available in case of emergency. Respiratory |
| | protective device with particle filter. |
| Hand protection: | Protective gloves. |
| Eye protection: | Safety glasses. Ensure eye bath is to hand. |
| Skin protection: | Protective clothing. |
| | |

Section 9: Physical and chemical properties

BRIWAX ORIGINAL WAX POLISH

9.1. Information on basic physical and chemical properties

| State: | Wax | |
|-------------------------------|---|--------------------|
| Colour: | Off-white | |
| Odour: | Characteristic odour | |
| Evaporation rate: | No data available. | |
| Oxidising: | No data available. | |
| Solubility in water: | Insoluble | |
| Also soluble in: | Benzene. | |
| Viscosity: | Viscous | |
| Boiling point/range°C: | No data available. Melting point/range°C: | No data available. |
| Flammability limits %: lower: | No data available. upper: | No data available. |
| Flash point°C: | 21 Part.coeff. n-octanol/water: | No data available. |
| Autoflammability°C: | No data available. Vapour pressure: | No data available. |
| Relative density: | No data available. pH: | Approx. 7 |
| VOC g/l: | No data available. | |

9.2. Other information

Other information: No data available.

Section 10: Stability and reactivity

10.1. Reactivity

Reactivity: Stable under recommended transport or storage conditions.

10.2. Chemical stability

Chemical stability: Stable under normal conditions.

10.3. Possibility of hazardous reactions

Hazardous reactions: Hazardous reactions will not occur under normal transport or storage conditions.

Decomposition may occur on exposure to conditions or materials listed below.

10.4. Conditions to avoid

Conditions to avoid: Heat.

10.5. Incompatible materials

Materials to avoid: Strong oxidising agents. Strong acids.

10.6. Hazardous decomposition products

Haz. decomp. products: In combustion emits toxic fumes.

Section 11: Toxicological information

Page: 5

BRIWAX ORIGINAL WAX POLISH

11.1. Information on toxicological effects

Hazardous ingredients:

TOLUENE

| IVN | RAT | LD50 | 1960 | mg/kg |
|-----|-----|------|------|-------|
| ORL | MUS | LD50 | 2 | gm/kg |
| ORL | RAT | LD50 | 6900 | mg/kg |

Relevant hazards for product:

| Hazard | Route | Basis |
|---------------------------|-------|-----------------------|
| Skin corrosion/irritation | DRM | Hazardous: calculated |
| Reproductive toxicity | | Hazardous: calculated |
| STOT-single exposure | - | Hazardous: calculated |
| STOT-repeated exposure | - | Hazardous: calculated |

Symptoms / routes of exposure

Skin contact: There may be irritation and redness at the site of contact.

Eye contact: There may be irritation and redness. The eyes may water profusely.

Ingestion: There may be soreness and redness of the mouth and throat.

Inhalation: There may be irritation of the throat with a feeling of tightness in the chest. Exposure may cause coughing or wheezing.

Delayed / immediate effects: Immediate effects can be expected after short-term exposure.

Section 12: Ecological information

12.1. Toxicity

Ecotoxicity values: No data available.

12.2. Persistence and degradability

Persistence and degradability: Biodegradable.

12.3. Bioaccumulative potential

Bioaccumulative potential: No bioaccumulation potential.

12.4. Mobility in soil

Mobility: Readily absorbed into soil.

12.5. Results of PBT and vPvB assessment

PBT identification: This product is not identified as a PBT/vPvB substance.

12.6. Other adverse effects

Other adverse effects: Negligible ecotoxicity.

BRIWAX ORIGINAL WAX POLISH

Section 13: Disposal considerations

13.1. Waste treatment methods

Disposal operations: Transfer to a suitable container and arrange for collection by specialised disposal company.

NB: The user's attention is drawn to the possible existence of regional or national regulations regarding disposal.

Section 14: Transport information

14.1. UN number

UN number: UN1263

14.2. UN proper shipping name

Shipping name: PAINT

including paint, lacquer, enamel, stain, shellac, varnish, polish, liquid filler and liquid

Marine pollutant: Yes

lacquer base

14.3. Transport hazard class(es)

Transport class: 3

14.4. Packing group

Packing group: ||

14.5. Environmental hazards

Environmentally hazardous: No

14.6. Special precautions for user

Special precautions: No special precautions.

Tunnel code: D/E

Transport category: 2

Section 15: Regulatory information

15.1. Safety, health and environmental regulations/legislation specific for the substance or mixture

Specific regulations: Not applicable.

15.2. Chemical Safety Assessment

Chemical safety assessment: A chemical safety assessment has not been carried out for the substance or the mixture by the supplier.

Section 16: Other information

BRIWAX ORIGINAL WAX POLISH

| Other information | |
|------------------------------|--|
| Other information: | according to Regulation (EC) No. 1907/2006 (REACH) with its amendment Regulation (EU) 2015/830 |
| | * indicates text in the SDS which has changed since the last revision. |
| Phrases used in s.2 and s.3: | H224: Extremely flammable liquid and vapour. |
| | H225: Highly flammable liquid and vapour. |
| | H304: May be fatal if swallowed and enters airways. |
| | H315: Causes skin irritation. |
| | H336: May cause drowsiness or dizziness. |
| | H361d: Suspected of damaging the unborn child. |
| | H373: May cause damage to organs through prolonged or repeated exposure. |
| Legal disclaimer: | The above information is believed to be correct but does not purport to be all inclusive |
| | and shall be used only as a guide. This company shall not be held liable for any |
| | damage resulting from handling or from contact with the above product. |